

# Alpha modular spreader beam system

## Order form

### Chose your model

☐ **rigid** (reference number 476635)



☐ **adjustable** (reference number 476633)



### Required load capacity

- |                                    |                                    |                                    |                                    |                                    |                                    |                                    |
|------------------------------------|------------------------------------|------------------------------------|------------------------------------|------------------------------------|------------------------------------|------------------------------------|
| <input type="checkbox"/> 1.000 kg  | <input type="checkbox"/> 1.500 kg  | <input type="checkbox"/> 2.000 kg  | <input type="checkbox"/> 2.500 kg  | <input type="checkbox"/> 3.000 kg  | <input type="checkbox"/> 3.500 kg  | <input type="checkbox"/> 4.000 kg  |
| <input type="checkbox"/> 4.500 kg  | <input type="checkbox"/> 5.000 kg  | <input type="checkbox"/> 6.000 kg  | <input type="checkbox"/> 7.000 kg  | <input type="checkbox"/> 8.000 kg  | <input type="checkbox"/> 9.000 kg  | <input type="checkbox"/> 10.000 kg |
| <input type="checkbox"/> 11.000 kg | <input type="checkbox"/> 12.000 kg | <input type="checkbox"/> 13.000 kg | <input type="checkbox"/> 14.000 kg | <input type="checkbox"/> 15.000 kg | <input type="checkbox"/> 16.000 kg |                                    |
| <input type="checkbox"/> 17.000 kg | <input type="checkbox"/> 18.000 kg | <input type="checkbox"/> 19.000 kg | <input type="checkbox"/> 20.000 kg |                                    |                                    |                                    |

### Maximum working lengths

- |                                   |                                   |                                   |                                   |                                   |                                   |
|-----------------------------------|-----------------------------------|-----------------------------------|-----------------------------------|-----------------------------------|-----------------------------------|
| <input type="checkbox"/> 1.000 mm | <input type="checkbox"/> 1.500 mm | <input type="checkbox"/> 2.000 mm | <input type="checkbox"/> 2.500 mm | <input type="checkbox"/> 3.000 mm | <input type="checkbox"/> 3.500 mm |
| <input type="checkbox"/> 4.000 mm | <input type="checkbox"/> 4.500 mm | <input type="checkbox"/> 5.000 mm | <input type="checkbox"/> 5.500 mm | <input type="checkbox"/> 6.000 mm |                                   |

Notice: the minimum working lengths for the adjustable version results automatically from the max. working lengths and grid spacing!

### Grid spacing\*

- ☐ 100 mm   ☐ 150 mm   ☐ 200 mm   ☐ 250 mm   \*relevant only for the adjustable version

### Crane hook size

Single crane hook according to DIN 15401

- ☐ EH 1,6   ☐ EH 2,5   ☐ EH 4   ☐ EH 5   ☐ EH 6   ☐ EH 8   ☐ EH 10   ☐ EH 12   ☐ EH 16  
☐ EH 20   ☐ EH 25

### Additional options



- ☐ **Attachment lugs**  
for 2-leg chain suspension gear incl. shackles (2 pcs.)



- ☐ **Additional attachment lugs with load hooks**  
(2 pcs)  
Only with rigid version!



- ☐ **Gaps for fork lift truck prongs –**  
can be bolted to the underside of the profile (2 pcs)



- ☐ **Adjustable stirrups**  
(2 pcs)  
Only with adjustable version!



- ☐ **Feet for stocking –**  
can be bolted to the ends (2 pcs)

### Customer

Company:

Address:

Contact name:

Phone:

E-mail:

Complete, scan or take a photo of the form and send by email to:  
**traverse@pfeifer.info**

By fax to:  
**+49 8331 937-380**

Even simpler and faster –  
configure and order online:  
**www.pfeifer.info/traverse**

For questions by telephone:  
**+49 8331 937-112**

### Our promise:

- Quotation and construction drawing within 24 hours
- Dispatch within 3 days\* after ordering

\* Ready for dispatch within 3 working days from receipt of order by PFEIFER